

# CHANNEL ESTIMATOR AND METHOD FOR ESTIMATING A CHANNEL TRANSFER FUNCTION AND APPARATUS AND METHOD FOR PROVIDING PILOT SEQUENCES

Bibliographic data	Description	Claims	Mosaics	Original document	INPADOC legal status
<b>Publication number:</b> <b>Publication date:</b> 2007-08-16 <b>Inventor(s):</b> <b>Applicant(s):</b> DO-COMO COMMUNICATIONS LABORATORIES <b>Classification:</b> - <b>international:</b> H04J11/00; H04B7/04; H04L25/02; H04L27/26; H04B7/06; H04J11/00; H04B7/04; H04L25/02; H04L27/26 - <b>European:</b> H04L25/02C7C1A; H04B7/04; H04L25/02C3C; H04L27/26M1R1; H04L27/26M1R3; H04L27/26M5 <b>Application number:</b> JP20060553442T 20040219 <b>Priority number(s):</b> WO2004EP01645 20040219					<b>Also published as:</b> WO2005081481 (A1) EP1716680 (A1) EP1716680 (B1)
<a href="#">View INPADOC patent family</a> <a href="#">View list of citing documents</a> <a href="#">Report a data error here</a>					

Abstract not available for JP 2007523550 (T)

Abstract of corresponding document: **WO 2005081481 (A1)**

A Channel estimator for estimating a channel transfer function of a communication channel from a receive signal including a pilot sequence being transmittable from a transmitting point to a receiving point through the communication channel, wherein the pilot sequence is designed such that a spectral representation of the pilot sequence occupies a band-pass spectral region having a predetermined center frequency comprises a band-pass filter having the predetermined center frequency for filtering a spectral representation of the receive signal to obtain a filtered transformed signal, wherein the filtered transformed signal comprises an estimate of the channel transfer function. Therefore, an efficient channel estimation scheme for multiple input multiple output systems is provided.

Data supplied from the **esp@cenet** database — Worldwide